

Features

- ◇ Small size, simple structure, easy to maintain.
- ◇ 6 vacuum ports for several suction cups.
- ◇ With built-in silencer.
- ◇ Various vacuum cartridges are available for different applications.
- ◇ Slotted structure for quick installation.



Applications

- ◇ 3C Industry
- ◇ Packaging
- ◇ Sheet metal
- ◇ Logistics

How to order

AGP - S08-3

① ②

① Series	② Specification
AGP	S08-3 (-75kPa) X10-3 (-93kPa) P12-3 (-90kPa)

Vacuum flow(NL/min) at different vacuum levels(-kPa)

Model	Air supply pressure(bar)	Air consumption (NL/min)	0	10	20	30	40	50	60	70	80	Max.vacuum level (-kPa)
AGP-S08-3	4.5	19	60	38	24	14.9	11.5	6.8	-	-	-	60
	5.0	23	66	40	32	19.1	13.3	9.9	6.5	-	-	70
	6.0	27	68	42	36	24	13	10.2	8.4	6.3	-	75
AGP-X10-3	4.5	27.5	64	40	32	18	11.3	9.7	7.3	4.9	2.7	90
	5.0	30	66	40	34	24	14.3	9.3	6.9	4.8	2.4	93
	6.0	34.5	68	44	34	30	20	10.5	6.5	4.9	1.7	91
AGP-P12-3	1.7	19	46	19.8	10.5	7	3	-	-	-	-	43
	2.2	22.5	52	30	12	8.2	5.8	2.7	-	-	-	58
	3.14	29	62	38	28	10	7.7	6.7	4.8	2.9	1.4	90
	4.0	35	68	40	34	24	11.4	5.7	4.2	3.0	1.2	88

Evacuation time(s/L) to reach different vacuum levels(-kPa)

Model	Air supply pressure(bar)	Air consumption (NL/min)	10	20	30	40	50	60	70	80	Max.vacuum level (-kPa)
AGP-S08-3	4.0	19	0.06	0.22	0.53	0.93	1.72	4.61	-	-	60
	5.0	23	0.06	0.19	0.44	0.83	1.35	2.23	6.33	-	70
	6.0	27	0.05	0.19	0.38	0.68	1.26	2.08	3.05	-	75
AGP-X10-3	4.5	27.5	0.06	0.19	0.40	0.76	1.45	2.21	3.49	5.55	90
	5.0	30	0.05	0.19	0.37	0.66	1.26	2.14	3.45	5.60	93
	6.0	34.5	0.05	0.18	0.35	0.59	1.02	2.10	3.31	5.72	91
AGP-P12-3	1.7	19	0.13	0.52	1.22	2.75	-	-	-	-	43
	2.2	22.5	0.08	0.31	0.70	1.33	2.54	-	-	-	59
	3.14	29	0.06	0.21	0.45	0.94	1.58	2.40	3.83	6.07	90
	4.0	35	0.06	0.20	0.38	0.67	1.26	2.36	3.75	6.57	88

Dimensions (mm)
