

Features

- ◇ Small size, simple structure, easy to maintain.
- ◇ Vacuum port M5, can be directly mounted with level compensator.
- ◇ It reduces reaction time by shortening vacuum flow channel.
- ◇ Various vacuum cartridges are available for different applications.



Applications

- ◇ 3C Industry
- ◇ Sheet metal
- ◇ Packaging
- ◇ Logistics

How to order

AGL - X

Vacuum flow(NL/min) at different vacuum levels(-kPa)

Model	Air supply pressure(bar)	Air consumption (NL/min)	0	10	20	30	40	50	60	70	Max.vacuum level (-kPa)
AGL-X	4.5	9	14.9	9.9	4.8	4.1	3.3	2.6	1.7	-	85
	5.0	9.5	15.6	11.6	6.6	4.0	3.3	2.6	1.7	-	90
	6.0	10	17.2	14.2	9.3	4.5	3.3	2.3	1.4	-	89

Evacuation time(s/L) to reach different vacuum levels(-kPa)

Model	Air supply pressure(bar)	Air consumption (NL/min)	10	20	30	40	50	60	70	80	Max.vacuum level (-kPa)
AGL-X	4.5	9	0.4	1.3	3.2	4.6	6.5	9.8	15.3	25.70	85
	5.0	9.5	0.3	0.9	2.4	4.3	6.7	9.8	14.1	22.03	90
	6.0	10	0.2	0.7	1.3	3.7	5.9	9.5	14.5	22.41	89

Dimensions(mm)

