

Features

- ◇ Straight through design, one-touch fitting, with bracket, easy assemble.
- ◇ Small size and light weight.
- ◇ Transparent housing, easy to indicate the degree of contamination.
- ◇ Filter element is replaceable.



Applications

- ◇ Suitable for vacuum system with light or medium dirt level.

How to order

ZFA 50 - 04 B



① ② ③ ④

① Series	② Vacuum flow	③ Hose diameter	④ Bracket
ZFA	50 - Max 10NL/min	02 - $\phi 2$ Hose 03 - $\phi 3.2$ Hose 04 - $\phi 4$ Hose	B - Default, with bracket


Technical parameters

Model	Applicable hose O.D.(mm)	Nominal flow (NL/min)	Fluid	Operating pressure (kPa)	Removal efficiency (μm)	Ambient and fluid temperature($^{\circ}\text{C}$)	Element differential pressure resistance (bar)	Applicable hose material
ZFA50-02	$\phi 2$	2	Air	-100~0	10	0~60	1.5	Nylon
ZFA50-03	$\phi 3.2$	7	Nitrogen					PU
ZFA50-04	$\phi 4$	10						

Applications



Dimensions(mm)



Model/ Size	A	B	C	D	E	F	G	H	I	J	K	L
ZFA50-02B	59.5	13	33	13	25	10	6	10.5	11.5	8.5	13.5	2
ZFA50-03B	59.5	11.5	33	11.5	25	10	-	10.5	11.5	8.5	13.5	3.2
ZFA50-04B	59.5	12.8	33	12.8	25	10	-	10.5	11.5	8.5	13.5	4

Repair kits



Model of filter element	Applicable vacuum filter
ZFA50-FE	ZFA50-02 , 50-03 , 50-04