





规格 Specifications

1. 相数 Number of Phase	2
2. 步距角 Step Angle	1.8°
3. 额定电压 Rated Voltage	2.33 V DC
4. 额定电流 Rated Current	3.7 Amp
5. 保持力矩 Holding Torque	1.35 N.m Typ.(Two phase on/rated current)
6. 相电阻 Phase Resistance	0.63±0.1ohm(20°C)
7. 相电感 Phase Inductance	2.0 mH±20%(1kHz 1V rms)
8. 转子惯量 Rotor Inertia	260 g.cm^2
9. 电机重量 Motor Weight	600 g
10. 绝缘等级 Insulation Class	B(130°C)

接线图
Wiring Diagram



励磁顺序vs.旋转方向
Exciting Sequence vs. Direction of Rotation

STEP	A	B	C	D	
1	+	+	-	-	CCW ↑ CW ↓
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	

从安装面看为顺时针方向
Clockwise view from mouting side

标签 Label Detail

前8位XXXXXXXX--work order 加工单号
后4位XXXX--serial number 流水号



F			Unit: mm				MOONS'		Hybrid Stepping Motor		F				
			第一角画法 FIRST ANGLE METHOD		批准 Approve			SHANGHAI AMP & MOONS' AUTOMATION CO.,LTD							
			未注线性与角度尺寸公差 Tolerances for linear and angular dimensions without individual tolerance indications		标准化 Standard										
			GB/T 1804-m eqv ISO 2768-1 : m		工艺 Technology			This document is released for information only. Its reproduction in whole or in part or its dissemination to third parties is prohibited. All trademarks and registered trademarks appearing on this document are the property of their respective owners.							
			未注形状与位置尺寸公差 Geometrical tolerance for features without individual tolerance indications		审核 Check										
			GB/T 1184-K eqv ISO 2768-2 : K		设计 Design										
REV.	原始版本 Original revision		版本记录 REVISION RECORD	DATE	UNLESS OTHERWISE SPECIFIED	NAMES	SIGNATURE	DATE	Type: AM23HS2450-01	Rev.A	SCALE 1:1	Sheet 1 of 1			
1		2		3		4		5		6		7		8	