





4611110028033



接线图

Wiring Diagram



励磁顺序vs.旋转方向



Exciting Sequence vs. Direction of Rotation

STEP	A	B	C	D	CCW
1	+	+	-	-	↑
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	

从安装面看为顺时针方向
Clockwise view from mounting side

规格 Specifications

1. 相数 Number of Phase	2
2. 步距角 Step Angle	1.8°
3. 额定电压 Rated Voltage	1.58 V DC
4. 额定电流 Rated Current	6.3 Amp
5. 保持力矩 Holding Torque	3.7 Nm Typ.(Two phase on/rated current)
6. 相电阻 Phase Resistance	0.25 ±0.1 ohm(20°C)
7. 相电感 Phase Inductance	1.9 mH±20%(1kHz 1V rms)
8. 转子惯量 Rotor Inertia	1100 gcm ²
9. 电机重量 Motor Weight	1.6 kg
10. 绝缘等级 Insulation Class	B(130°C)

电缆线断面
Cable section

外被Jacket
无纺布Non-woven
填充物Fillers
导体Conductor



★ 备注 Comment:

- 1.使用 NSK密封轴承
- 2.黑端盖

铭牌 Label Detail


XXXXXXXX- work order 加工单号
XXXX- serial number 流水号

MOONS' STEPPING MOTOR
TYPE: AM34HD0404-M08
MADE IN CHINA YY/MM/DD
XXXXXXXX-XXXX



Date Format
日期格式

Unit: mm
第一角画法
FIRST ANGLE METHOD
未注线性与角度尺寸公差
Tolerances for linear and angular dimensions without
individual tolerance indications
GB/T 1804-m eqv ISO 2768-1 : m
未注形状与位置尺寸公差
Geometrical tolerance for features without
individual tolerance indications
GB/T 1184-K eqv ISO 2768-2 : K



批准 Approve	张书峰	11.29
标准化 Standard	张书峰	11.29
工艺 Technology	张书峰	11.29
审核 Check	张书峰	11.29
设计 Design	张书峰	2017.11.29

MOONS'

Hybrid Stepping Motor

Shanghai Moons' Electric Co., Ltd.

This document is released for information only. Its reproduction in whole or in part or its dissemination to third parties is prohibited. All trademarks and registered trademarks appearing on this document are the property of their respective owners.

REV.	原始版本 Original revision	2017.11.29	UNLESS OTHERWISE SPECIFIED	NAMES	SIGNATURE	DATE	Type: AM34HD0404-M08	Rev.A	SCALE 1:2	Sheet 1 of 1
------	------------------------	------------	----------------------------	-------	-----------	------	----------------------	-------	-----------	--------------